



Rack Conveyor Dishwashers



Introducing the new Heavy Duty Rack Conveyors from DC, high performance machines capable of delivering outstanding results time and time again.



- Heavy duty
- Fast
- Reliable
- Durable
- Digital



Performance

Fast throughput
from 70 to 148 racks per hour

Water consumption
of 1.2 litres per rack

Quick response
digital thermostats speed machine reactions

Increased usable height
accommodates larger items such as trays, pots and utensils

Energy and Cost Savings

Low water usage
reduces water consumption and chemical costs

Insulated counter balanced doors
aiding operator loading and reducing energy wastage

Economiser function
reduces running costs by cutting energy consumption and reducing emissions

Insulated boiler
improves heat retention and boiler recovery times

Steam recovery (optional)
reduces energy consumption by using recovered steam to preheat inlet water

Operation

Intuitive, simple digital control panel
reduces user error and staff training

EasyClean filter system
filters remove debris and protects vital components

Temperature read outs
wash and boiler temperature read outs assist machine management

Chemical auto dosing (optional)
eliminates user intervention and prevents over or under dosing

Welcome to a Cleaner World

Rack Conveyor Specifications



	DCX500	DCX600
Racks per hour	70/95	95/148
Baskets (x3)	500 x 500 mm	500 x 500 mm
Height	1450 mm	1450 mm
Width	1150 mm	1650 mm
Depth	795 mm	795 mm
Usable wash height	430 mm	430 mm
Drain height	170 mm	170 mm
Wash tank volume	80 L	125 L
Rinse water consumption	147 L p/h	200 L p/h
Total load	19.1 kW	23.9 kW
Amps per phase	29 Amps	36 Amps
Required water flow rate	10 L p/min	10 L p/min
Internal softener*	Optional	Optional
Break tank (WRAS)	Standard	Standard

Rack Conveyor Add-Ons

Description	Compatible models	Amps per phase	Code
Electric drying module - 6kW - adds 600mm to machine width and 495mm to the height	All models	10	RXD6
Corner drying module - 6kW - adds 1000mm to machine width and 335mm to the depth	All models	10	RXCD6
Steam condenser heat recovery module - adds 570mm to machine height	All models	1	RXSHR
Configuration for cold water supply	DCX500	18	RXCW1
Configuration for cold water supply	DCX600	22	RXCW2
Splash guard - fixed - adds 200mm to machine width	All models	-	RXSPG
Splash guard - fixed - with spigot - adds 200mm to machine width	All models	-	RXSPGSP
Splash guard - floating - adds 200mm to machine width	All models	-	RXSPGFL
Splash guard - floating – with spigot - adds 200mm to machine width	All models	-	RXSPGFLSP
Detergent and rinse aid dosing pumps (supply only)	All models	-	RXDP
Detergent and rinse aid dosing pumps (fitted)	All models	-	RXDP-1
End stop	All models	-	RXES
Drain Pump – one required for each washtank	All models	-	RXLDP

Where water hardness exceeds 100ppm a water softener is required.

Warranty: One year parts and labour. Extended warranties available - please ask your supplier.

We reserve the right to change specifications without notice.



DC Products

Unit 25 Lodge Hill Industrial Park, Westbury Sub Mendip, Somerset, BA5 1EY

t: +44 (0)1749 870055 f: +44 (0)1749 870056 e: sales@dcproducts.co.uk www.dcprouducts.co.uk

