



Optima Glasswashers

Introducing the new Optima Range Glasswashers from DC, specifically designed to meet the rigorous demands of all UK catering outlets.



- **Advanced**
- **Economical**
- **Environmentally friendly**
- **Robust**



Performance

Superior washing performance
with reduced running costs

Five cycles to choose from
including one sanitising cycle to AO60

Heavy duty wash pumps
deliver optimum wash results

Digital heat sensors and up-rated heating elements
maintain perfect wash and rinse temperatures

Energy and Cost Savings

Double skinned and insulated cabinet and door and insulated boiler
reduces noise and heat emissions whilst lowering running costs

Low volume wash tank
saves up to 13000L¹ of water p/a

Reduced water consumption
produces the optimum balance between water usage and hygiene

Standby mode
automatically lowers machine temperatures when not in use for extended periods

Operation

Intuitive, simple, touch screen interface
with temperature readouts

Chemical dosing adjustment
administered via the control panel

WRAS-approved break tank and drain pump
as standard

Superior peristaltic dosing units
for improved accuracy

Welcome to a Cleaner World

Optima Range Glasswasher Specifications



	OXG50AD
Cycle time	120 180 240 480 Eco cycle
Baskets (x2)	500 x 500 mm
Height	730 mm
Width	600 mm
Depth	600 mm
Depth with door open	
Usable wash height	300 mm
Drain Ø	65 mm
Wash tank	12 L
Boiler	5.5 L
Water usage	2.5 L p/c
Wash element	2 kW
Boiler element	6 kW
Total load	6.6 kW
Amps required ²	30 Amps
Detergent dosing	Yes
Rinse aid dosing	Yes
Water connection	3/4 BSP
Required water pressure	2-4 bar
Required water flow rate	10 L p/min
Drain pump	Standard
Internal softener ³	Optional
Break tank (WRAS)	Standard

Where water hardness exceeds 100ppm a water softener is required.

¹ Based on a two service day and on the OXG50 glasswasher compared with traditional wash tank models.

² 30A machines can be derated to 20A or 13A upon request

³ Internal water softener is not suitable for hot water above 30°C. Softening capacity between regenerations is 250 litres @ 300ppm. Where water hardness exceeds 300ppm and the daily wash cycles exceed 80 per day an alternative softener may be required - please contact your supplier for further information.

Warranty: One year parts and labour. Extended warranties available - please ask your supplier.

We reserve the right to change specifications without notice.



DC Products

Unit 25 Lodge Hill Industrial Park, Westbury Sub Mendip, Somerset, BA5 1EY

t: +44 (0)1749 870055 f: +44 (0)1749 870056 e: sales@dcproducts.co.uk www.dcprouducts.co.uk

