



# Pot Washers



DC Pot and Utensil Washers from DC, specifically designed to accommodate a wide range of pots, pans, utensils, containers, gastronorm and baking trays.



- Robust
- Economical
- Flexible
- Productive



## Performance

**Break tank - WRAS approved**  
should be fitted to machines that are to be used as commercial dishwashers and connected to the mains water supply

**EasyClean filter system**  
maintenance friendly filters protect critical components

**Self draining wash pump for improved hygiene**  
increases wash pressure improving results

## Energy and Cost Savings

**Double-skinned construction**  
reduces noise and heat emissions whilst lowering running costs

**Removable anti-block wash and rinse arms**  
provides ultimate rinse coverage and increases initial response by 30% and rotation speed by 20%

**Insulated boiler**  
improves heat retention and boiler recovery times

**Reduced water consumption**  
produces the optimum balance between water usage and hygiene

## Operation

**Comes with variable (and customisable) cycle times**  
for maximum productivity

**Simple intuitive user interface and controls**  
reduce user error and staff training

**Selectable operation speeds**  
allowing simple customisation

**Moulded wash tank**  
prevents debris build-up and assists routine maintenance

**Boiler and wash tank temperature displays**  
provide ease-of-mind when in use

*Welcome to a Cleaner World*

# Pot Washer Specifications



	DC57-42A	DC57-62A	DC67A	DC109A
<b>Cycle time</b>	60 120 150 480 sec	60 120 180 480 sec	180 360 540 600 sec	180 360 540 600 sec
<b>Baskets (x2)</b>	570 x 620 mm	570 x 620 mm	670 x 670 mm	1150 x 615 mm
<b>Height</b>	1368 mm	1690 mm	2160 mm	2160 mm
<b>Width</b>	670 mm	685 mm	855 mm	1335 mm
<b>Depth</b>	725 mm	720 mm	820 mm	785 mm
<b>Depth with door open</b>	1185 mm	1230 mm	1330 mm	1295 mm
<b>Usable wash height</b>	420 mm	620 mm	840 mm	840 mm
<b>Drain height</b>	65 mm	250 mm	130 mm	130 mm
<b>Wash tank</b>	20 L	30 L	55 L	96 L
<b>Water usage</b>	2.6 L	2.6 L	4.5 L	8.0 L
<b>Wash element</b>	2.5 kW	3.0 kW	6.0 kW	8.0 kW
<b>Boiler element</b>	6.0 kW	6.0 kW	9.0 kW	12.0 kW
<b>Total load</b>	6.5 kW	6.75 kW	12.2 kW	16.0 kW
<b>Amps required</b>	32A*	32A*	3N Min: 20** Max: 29	3N Min: 26** Max: 38
<b>Detergent dosing</b>	Optional	Optional	Optional	Optional
<b>Rinse aid dosing</b>	Optional	Optional	Optional	Optional
<b>Water connection</b>	3/4 BSP	3/4 BSP	3/4 BSP	3/4 BSP
<b>Required water pressure</b>	2-4 bar	2-4 bar	2-4 bar	2-4 bar
<b>Required water flow rate</b>	10 L per/min	10 L per/min	10 L per/min	10 L per/min
<b>Drain pump</b>	Optional	Optional	Optional	Optional
<b>Internal softener*</b>	Optional	Optional	NA	NA
<b>Break tank (WRAS)</b>	Included	Included	Included	Included

Where water hardness exceeds 100ppm a water softener is required.

\* Three-phase (3N) configuration available upon request.

\*\* The minimum amps per phase is based on a boiler priority configuration. The maximum amps per phase is based on the boiler and wash tank elements working in tandem.

Additional charges may apply for pot and utensil washer delivery.

**Warranty:** One year parts and labour. Extended warranties available - please ask your supplier.

We reserve the right to change specifications without notice.