



Premium Dishwashers



Introducing the new Premium Range Glasswashers from DC, specifically designed to meet the rigorous demands of all UK catering outlets.



- **Fast**
- **Heavy Duty**
- **Energy Efficient**
- **Economical**
- **Soft touch controls**
- **Temperature readouts**



Performance

My Wash cycle

four fixed and one self configurable cycles

Heavy duty wash pump

increases wash pressure improving results

Heavy duty heater element

faster start up and improved heater recovery times

Rinse thermo-lock

delivers perfect rinse temperatures time after time

Increased usable height

accommodates specialist dishware

Energy and Cost Savings

Low volume wash tank

saves up to 13000L* of water p/a

Reduced electrical costs

due to water reduction less energy is required to heat the machine

Double skinned & insulated door

further reduces noise and heat emissions lowering running costs

Improved rinse arms

increases initial response by 30% and rotation speed by 20%

Insulated boiler

lowers running costs and improves boiler recovery times

Operation

Intuitive, simple digital controls

complete with manager menu and temperature readouts

Counter balanced door

makes loading and unloading easier for the operator

Chemical auto-dosing

controlled via interface, improves results and prevents over or under dosing

Auto drain down (optional)

ensures rapid drain down with no need for user intervention

Integral water softener (optional)

softens water without the need for an external unit

'Welcome to a cleaner world'

Premium Range Dishwasher Specifications

18



	PD50
Cycle time	90 120 180 300 User Defined
Baskets (x3)	500 x 500 mm
Height	840 mm
Width	605 mm
Depth	635 mm
Depth with door open	1050 mm
Usable wash height	345 mm
Drain height	80 mm
Drain Ø	25 mm
Wash tank	12 lts
Boiler	5 lts
Water usage	2.6 lts p/c
Wash element	2.0 kW
Boiler element	6.0 kW
Total load	6.55 kW
Amps required	30 Amps**
Detergent dosing	Yes
Rinse aid dosing	Yes
Water connection	3/4 BSP
Required water pressure	2-4 bar
Required water flow rate	10 lts p/min
Drain pump	Optional
Internal softener*	Optional
Break tank (WRAS)	Optional

Where water hardness exceeds 100ppm a water softener is required.

* Based on a 2 service day and on the PD50 dishwasher compared with traditional wash tank models.

** Can be configured to operate on either 13A, 25A or 3Ph+N upon request.

*** Internal water softener is not suitable for hot water above 30°C.
Softening capacity between regenerations is 125 litres @ 300ppm.
Where water hardness exceeds 300ppm and the daily wash cycles exceed 40 per day an alternative softener may be required - please contact your supplier for further information.

Warranty: One year parts and labour. Extended warranties available - please ask your supplier.

We reserve the right to change specifications without notice.



DC Products

Unit 25 Lodge Hill Industrial Park, Westbury Sub Mendip, Somerset, BA5 1EY

t: +44 (0)1749 870055 f: +44 (0)1749 870056 e: sales@dcproducts.co.uk www.dcprouducts.co.uk

