



Premium Passthrough Dishwashers



Introducing the new Premium Range Passthroughs from DC, specifically designed to meet the rigorous demands of all UK catering outlets.



- **Energy Efficient**
- **Reliable**
- **Economical**
- **Adaptable**



Performance

My Wash cycle

four fixed and one self configurable cycles

Hood auto-start

increases speed and productivity and reduces user intervention

Heavy duty heater elements

faster start up and improved heat recovery times

Rinse thermo-lock

delivers perfect rinse temperatures time after time

Increased usable height

accommodates larger items such as trays, pots and utensils

Energy and Cost Savings

Low volume wash tank

reduces water consumption and chemical costs

Reduced electrical costs

low water usage requires less energy to heat the machine

Double skinned hood

further reduces noise and heat emissions lowering running costs

Improved rinse arms

increases initial response by 30% and rotation speed by 20%

Insulated boiler

improves heat retention and boiler recovery times

Operation

Intuitive, simple digital controls

complete with manager menu and temperature readouts

EasyClean filter system

three stage filter removes debris and protects vital components

Temperature read outs

wash and boiler temperature read-outs assist machine management

Colour status button

providing continual information

Integral water softener (optional)

softens water without the need for an external unit

'Welcome to a cleaner world'

Premium Range Passthrough Specifications



	PD1300	PD1350A
Cycle time	90 120 180 300 User Defined	90 120 180 300 User Defined
Baskets (x3)	500 x 500 mm	500 x 500 mm
Height	1500 mm	1500 mm
Height - hood raised	1950 mm	1950 mm
Width	655 mm	655 mm
Width including handle	750 mm	750 mm
Depth	745 mm	745 mm
Usable wash height	400 mm	400 mm
Drain height	410 mm	410 mm
Drain diameter Ø	32 mm	32 mm
Wash tank	28 lts	28 lts
Boiler	5 lts	9 lts
Water usage	2.6 lts p/c	2.6 lts p/c
Wash element	3.0 kW	3.0 kW
Boiler element	6 kW	10 kW
Total load	6.75 kW	11.1 kW
Amps required	32 Amps*	3N 18
Detergent dosing	Optional	Optional
Rinse aid dosing	Optional	Optional
Water connection	3/4 BSP	3/4 BSP
Required water pressure	2-4 bar	2-4 bar
Required water flow rate	10 lts p/min	10 lts p/min
Drain pump	Optional	Optional
Internal softener*	Optional	Optional
Break tank (WRAS)	Optional	Yes



Where water hardness exceeds 100ppm a water softener is required.

* Can be configured to operate on either 20A or 3Ph+N upon request.

** Internal water softener is not suitable for hot water above 30°C. Softening capacity between regenerations is 250 litres @ 300ppm. Where water hardness exceeds 300ppm and the daily wash cycles exceed 80 per day an alternative softener may be required - please contact your supplier for further information.

Warranty: One year parts and labour. Extended warranties available - please ask your supplier.

We reserve the right to change specifications without notice.



DC Products

Unit 25 Lodge Hill Industrial Park, Westbury Sub Mendip, Somerset, BA5 1EY

t: +44 (0)1749 870055 f: +44 (0)1749 870056 e: sales@dcproducts.co.uk www.dcprouducts.co.uk

