



# Standard Extra Glasswashers

Introducing the new Standard Extra Range Glasswashers from DC, specifically designed to meet the rigorous demands of all UK catering outlets.



## Standard Extra Range

SXG45  
SXG50



- **Fast**
- **Economical**
- **Energy Efficient**
- **Space Saving**



### Performance

**My Wash cycle**

four fixed and one self configurable cycles

**New innovative wash pump**

increases wash pressure improving results

**Hydrodynamic basket slides**

ensures optimum wash and rinse coverage

**Rinse thermo-lock**

delivers perfect rinse temperatures time after time

**Dual element configuration**

for faster start up and guaranteed wash temperatures

### Energy and Cost Savings

**Double skinned cabinet door**

reduces noise and heat emissions whilst lowering running costs

**Reduced water consumption**

produces the optimum balance between water usage and hygiene

**Improved rinse arms**

increases initial response by 30% and rotation speed by 20%

**Insulated boiler**

lowers running costs and improves boiler recovery times

**Standby mode**

reduces power usage when not in use

### Operation

**Intuitive, digital controls**

reduces user error and staff training

**EasyClean filters**

maintenance friendly filters protect critical components

**Chemical auto-dosing**

eliminates user intervention and prevents over or under dosing

**Auto drain down (optional)**

ensures rapid drain down with no need for user intervention

**Integral water softener (optional)**

softens water without the need for an external unit

'Welcome to a cleaner world'

## Standard Extra Range Glasswasher Specifications



	SXG45	SXG50
<b>Cycle time</b>	60 90 120 180 User Defined	60 90 120 180 User Defined
<b>Baskets (x2)</b>	450 x 450 mm	500 x 500 mm
<b>Height</b>	690 mm	690 mm
<b>Width</b>	525 mm	575 mm
<b>Depth</b>	545 mm	605 mm
<b>Depth with door open</b>	890 mm	950 mm
<b>Usable wash height</b>	310 mm	320 mm
<b>Drain height</b>	120 mm	120 mm
<b>Drain Ø</b>	25 mm	25 mm
<b>Wash tank</b>	18 lts	20 lts
<b>Boiler</b>	2.8 lts	2.8 lts
<b>Water usage</b>	2.4 lts p/c	2.4 lts p/c
<b>Wash element</b>	1.6 kW	1.6 kW
<b>Boiler element</b>	2.8 kW	2.8 kW
<b>Total load</b>	4.7 kW	4.7 kW
<b>Amps required</b>	20 Amps**	20 Amps**
<b>Detergent dosing</b>	Yes	Yes
<b>Rinse aid dosing</b>	Yes	Yes
<b>Water connection</b>	3/4 BSP	3/4 BSP
<b>Required water pressure</b>	2-4 bar	2-4 bar
<b>Required water flow rate</b>	10 lts p/min	10 lts p/min
<b>Drain pump</b>	Optional	Optional
<b>Internal softener*</b>	Optional	Optional



**Where water hardness exceeds 100ppm a water softener is required.**

\* Internal water softener is not suitable for hot water above 30°C. Softening capacity between regenerations is 125 litres @ 300ppm. Where water hardness exceeds 300ppm and the daily wash cycles exceed 40 per day an alternative softener may be required - please contact your supplier for further information.

\*\* Can be configured to operate on either 13A or 3Ph+N upon request.

**Warranty:** One year parts and labour. Extended warranties available - please ask your supplier.

We reserve the right to change specifications without notice.



**DC Products**

Unit 25 Lodge Hill Industrial Park, Westbury Sub Mendip, Somerset, BA5 1EY

t: +44 (0)1749 870055 f: +44 (0)1749 870056 e: sales@dcproducts.co.uk [www.dcprouducts.co.uk](http://www.dcprouducts.co.uk)

